



312T

TELESCOPIC WHEEL LOADER

Compact Power. Maximum Control. Built for Real Work.

This compact yet versatile telescopic handler offers a 1.2-tonne lift capacity and 3.06m lift height within a compact 2.63m length and 1.25m width. Easy to transport and ideal for tight spaces, it handles harsh environments with its cab design, central articulation joint, anti-stall system and anti-slip valve for maximum traction. Powered by a reliable 24hp Kubota engine, twin gear pumps and Poclain drive motors, the Yardex 312T also features boom float, hand throttle and a premium proportional electro-hydraulic joystick for smooth, comfortable operation, backed by our UK & Irish parts & support network.

KEY FEATURES

- 1200kg lift capacity
- 3060mm max lift height
- Kubota 24hp Euro 5 engine
- Hydrostatic transmission(18kph) with Poclain drive motor
- Twin gear hydraulic pump
- Electro-hydraulic proportional joystick with single lever operation
- Anti-stall system & anti-slip traction control
- Electric parking brake
- Low noise, high visibility ergonomic cab
- Machine weight (nett): 1600kgs
- Dimensions: 2360mm (L) x 1250mm (W) x 2000mm (H)
- Turning radius: 20250mm



PERFORMANCE	Rated Load (kg)	1200
	Bucket Capacity m ³	0.38
	Machine Weight (kg)	1660
	Overall Length (mm)	2630
	Overall Width (mm)	1250
	Overall Height (mm)	2000
DIMENSIONS	Wheelbase (mm)	1312
	Min Turning Radius (mm)	2050
	Max Lifting Height (mm)	3060
	Max Dumping Height (mm)	3060
	Engine Brand	Kubota
	Tire Specification	26×12-12
ENGINE	Engine Model	D1105-E4B-CWL-1
	Displacement (cc)	1123
	Power (kW)	18.2
	Engine Speed (rpm)	3000
	Cylinders	3
	Cooling	Water Cooled
	Transmission	Hydrostatic
DRIVETRAIN	Max Driving Speed (km/h)	21
	Drive Pump Pressure (bar)	320
	Working Pump Flow (L/min)	50
	Steering	Articulated
	Service Brake	Hydrostatic
GENERAL	Parking Brake	Electric
	Tyre Size	26×12-12
	Fuel Type	Diesel